



Husky

CURB AND FARM HOSES

A tougher breed of hose for tough applications.

Husky is a recognized industry leader as a proven supplier of high-quality nozzles and accessories for service station fuel delivery systems. Now we're taking the next logical step by offering a tough breed of hoses that is up to the challenge of daily fuel dispensing. Introducing Husky Curb Pump Gasoline Hose and Premier Farm/Truck Hose – outstanding performance at a reasonable price. All Husky hoses offer unmatched quality, value, and efficiency. More reasons why, when it comes to fuel dispensing resources, Husky is a breed apart.



SPECIFICATIONS:

Tube: Black Nitrile
Cover: Black CPE, Smooth finish with static wire
Reinforcement: Multiple textile plies
Temp. Range: -40°F to +180°F

Softwall Gasoline Pump Hose, U.L. listed



- Multiple textiles plies of reinforcement for flexibility and kink resistance
- A static wire as a path to conduct a static electrical charge to ground
- Cover resistant to abrasion, cuts, oil and ozone
- Will not mar the finish of a vehicle
- U/L and U/L C Listed Assembled MH49026
- Meets U/L and U/L C (UL330/ULC) requirements
- For use with biodiesel (to B20 in dedicated service), diesel, gasoline and oil



SPECIFICATIONS:

Tube: Black Nitrile
Cover: Black CPE, Wrapped finish
Reinforcement: Single-wire braid wrap impression
Temp. Range: -40°F to +180°F

Whip Hoses Available

Wirebraid Gasoline Pump Hose, U.L. listed



- Steel wire braided reinforcement that reduces meter creep and provides superior strength, crush-resistant durability, kink resistance
- Path to conduct a static electrical charge to ground
- Cover resistant to abrasion, cuts, oil and ozone
- Will not mar the finish of a vehicle
- U/L and U/L C Listed Assembled MH49026
- Meets U/L and U/L C (UL330/ULC) requirements
- For use with biodiesel (to B20 in dedicated service), diesel, gasoline and oil



Husky

CURB AND FARM HOSES



SPECIFICATIONS:

Tube: Black Nitrile

Cover: Black CPE, Wrapped finish

Reinforcement: Two-wire braids with wire helix

Temp. Range: -40°F to +180°F

Whip Hoses Available

Hardwall-Helix Gasoline Pump Hose, U.L. listed



- Dual wire helix that reduces meter creep and provides full suction capability and kink resistance
- Path to conduct a static electrical charge to ground
- Cover is resistant to abrasion, cuts, oil and ozone
- Will not mar the finish of a vehicle
- Suitable for use with reeling devices or applications where retractable cables are employed
- U/L and U/L C Listed Assembled MH49026
- Meets U/L and U/L C (UL330/ULC) requirements
- For use with biodiesel (to B20 in dedicated service), diesel, gasoline and oil



SPECIFICATIONS:

Tube: NBR, RMA Class A

Cover: NBR/PVC RMA Class A

Reinforcement: Spiral high tensile strength polyester cord

Temp. Range: -20°F to +160°F

Farm Tank Gasoline Pump Hose

- Two spiral, high-tensile, polyester cord reinforcement with a NBR tube and NBR/PVC cover
- Oil and abrasion resistant
- Static wire hose is designed for use with electric pumps
- Engineered for dispensing gasoline, kerosene and oil from farm or barrel type pumps where U/L approval is not required
- Use in agriculture, industrial and construction maintenance applications



The performance and durability you need. The affordability you want. For complete details on Husky Curb Pump Gasoline Hose, contact your Husky sales representative or call us today!

2325 Husky Way • Pacific, MO 63069 • 800-325-3558 • info@husky.com • www.husky.com

